

WHAT IS CLAIMED IS:

1. An electronic watermark inserter for inserting an electronic watermark pattern or patterns for identifying a furnisher of a picture or image, termed "picture" collectively, into data of said picture, said inserter comprising:

5 an electronic watermark pattern inserter for inserting previously generated key information pattern or patterns into a picture or pictures into which said electronic watermark pattern or patterns have been inserted and for transmitting the resulting picture or pictures.

2. The electronic watermark inserter as defined in claim 1 wherein said key information patterns are arranged at preset intervals, and wherein, when inserted, said key information patterns are shifted in respective random directions.

3. The electronic watermark inserter as defined in claim 1 further comprising:

picture analysis means for analysing an input picture for determining the insertion strength of said electronic watermark
5 pattern into each pixel of said picture;

said electronic watermark pattern or patterns and said key information patterns being inserted in accordance with said insertion strength information.

4. The electronic watermark inserter as defined in claim 2 further comprising:

picture analysis means for analysing an input picture for

T09040 229880

5 pattern into each pixel of said picture;

said electronic watermark pattern or patterns and said key information patterns being inserted in accordance with said insertion strength information.

5. An electronic watermark detector for detecting an electronic watermark pattern or patterns for specifying a furnisher for a picture or image, termed "picture" collectively, inserted into data of said picture, comprising:

5 means for detecting a key information pattern or patterns inserted into said data of the picture along with an electronic watermark pattern or patterns;

means for generating parameters required for detecting the
electronic watermark pattern or patterns from the key
10 information as detected; and

means for detecting said electronic watermark pattern or patterns from said picture based on the parameters generated in said parameter generating means.

6. The electronic watermark detector as defined in claim 5 wherein the key information patterns comprise patterns that are arranged at a preset interval at the outset and that, when inserted, are shifted each in a random direction.

7. An electronic watermark system comprising;

an electronic watermark inserter for inserting an electronic watermark pattern or patterns for identifying a

furnisher of a picture or image, termed "picture" collectively,
 5 into data of said picture, said inserter comprising:

an electronic watermark pattern inserter for inserting
 previously generated key information pattern or patterns into a
 picture or pictures into which said electronic watermark pattern
 or patterns have been inserted and for transmitting the
 10 resulting picture or pictures, and

an electronic watermark detector for detecting an
 electronic watermark pattern or patterns for specifying a
 furnisher for a picture or image, termed "picture" collectively,
 inserted into data of said picture, comprising:

15 means for detecting a key information pattern or patterns
 inserted into said data of the picture along with an electronic
 watermark pattern or patterns;

means for generating parameters required for detecting the
 electronic watermark pattern or patterns from the key
 20 information as detected; and

means for detecting said electronic watermark pattern or
 patterns from said picture based on the parameters generated in
 said parameter generating means.

8. A method for inserting an electronic watermark pattern or
 patterns for identifying a furnisher of a picture or image,
 termed "picture" collectively, into data of said picture, said
 method comprising the steps of:

5 (a) providing a key information pattern or patterns,

(b) inserting the previously provided key information pattern or patterns into a picture or pictures, into which an electronic watermark pattern or patterns have been inserted, and

(c) transmitting the resulting picture or pictures.

9. The method as defined in claim 8 wherein said key information patterns are arranged at present intervals, and wherein, when inserted, said key information patterns are shifted in random directions, respectively.

10. The method as defined in claim 8 further comprising:

a step of analysing an input picture or pictures for determining the insertion strength of said electronic watermark pattern or patterns per each pixel or section of said picture or pictures;

a step of inserting said electronic watermark pattern or patterns and said key information pattern or patterns in accordance with said insertion strength information.

11. The method as defined in claim 7 further comprising:

a step of analysing an input picture or pictures for determining the insertion strength of said electronic watermark pattern or patterns per each pixel or section of said picture or pictures;

a step of inserting said electronic watermark pattern or patterns and said key information pattern or patterns in accordance with said insertion strength information.

12. A method for detecting an electronic watermark pattern for

103040-229300

specifying a furnisher for a picture or image, termed "picture" collectively, inserted into data of said picture, comprising the steps of:

5 (a) detecting key information pattern or patterns inserted into said data of the picture or pictures along with said electronic watermark pattern or patterns;

10 (b) generating parameters required for detecting the electronic watermark pattern or patterns from the key information pattern or patterns as detected; and

(c) detecting said electronic watermark pattern or patterns from said picture or pictures based on the parameters generated.

13. The method as defined in claim 12 wherein said key information patterns comprise patterns that are arranged at a present interval at the outset and that, when inserted, are shifted in a random direction, respectively.

14. An electronic watermark inserter for inserting an electronic watermark pattern or patterns for identifying a furnisher of a picture into data of said picture, said inserter comprising:

5 (a) an electronic watermark pattern inserter for inserting previously generated key information pattern into a picture or pictures into which said electronic watermark pattern has been inserted and for transmitting the resulting picture or pictures,

(b) means for providing said key information pattern in a

T090902 229860

10 predetermined specific arrangement of patterns, and

(c) means for shifting, upon insertion, said patterns in random directions, pattern by pattern.

15. The electronic watermark inserter as defined in claim 14 further comprising:

5 a picture analysis unit analysing an input picture for determining the insertion strength of said electronic watermark pattern into each pixel of said picture;

said electronic watermark pattern and said key information pattern being inserted in accordance with said insertion strength information.

16. An electronic watermark detector for detecting an electronic watermark pattern for specifying a furnisher for a picture inserted into data of said picture, comprising:

5 (a) a key information pattern detecting unit detecting a key information pattern inserted into said data of the picture along with an electronic watermark pattern;

(b) a parameter generator generating parameters required for detecting the electronic watermark pattern from the key information as detected;

10 (c) a watermark pattern detector detecting said electronic watermark pattern from said picture based on the parameters generated in said parameter generator.

17. The electronic watermark detector as defined in claim 16 wherein the key information pattern comprises patterns that are

"00000" 229360

arranged at a present interval at the outset and that, when inserted, are shifted each in a random direction.

18. A method for inserting an electronic watermark pattern or patterns for identifying a furnisher of a picture or image, termed "picture" collectively, into data of said picture, said method comprising the steps of:

5 (a) providing a key information pattern or patterns;

(b) inserting the previously provided key information pattern or patterns into a picture or pictures, into which an electronic watermark pattern or patterns have been inserted;

(c) transmitting the resulting picture or pictures;

10 wherein said key information patterns are arranged at present intervals, and wherein, when inserted, said key information patterns are shifted in random directions, pattern by pattern.

19. The method as defined in claim 18 further comprising:

a step of analysing an input picture or pictures for determining the insertion strength of said electronic watermark pattern or patterns per each pixel or section of said picture or
5 pictures;

a step of inserting said electronic watermark pattern or patterns and said key information pattern or patterns in accordance with said insertion strength information.

20. A method for detecting an electronic watermark pattern for specifying a furnisher for a picture inserted into data of said

20250101 22:29:30

picture, comprising the steps of:

(a) detecting key information pattern or patterns
5 inserted into said data of the picture or pictures along with
said electronic watermark pattern or patterns;

(b) generating parameters required for detecting the
electronic watermark pattern from the key information pattern as
detected; and

10 (c) detecting said electronic watermark pattern from said
picture based on the parameters generated,

wherein said key information pattern comprises patterns
that are arranged at a present interval at the outset and that,
when inserted, are shifted in a random direction, pattern by
15 pattern.